

RVS LED armaturen Ex de - type Z.1361 Stainless Steel LED lighting fixtures Ex de - type Z.1361

Technische informatie

Ex markering: II 2 G Ex db eb mb op is q IIC T5/T4 Gb
 II 2 D Ex tb IIIC T80°C Db

Geschikt voor zone 1 en 2

Omgevingstemperatuur: (T4): -25°C tot +55°C

Omgevingstemperatuur: (T5): -25°C tot +40°C

Bescherming: IP66

Spanning: 100~250 VAC - 50/60 Hz.

Lamp: 1 of 2 stuks LED unit 30 Watt - Kleur 5700 K

Kabelingangen: 3 stuks M25

Materiaal kap: Polycarbonate

Uitvoering met batterij tbv noodverlichting - alleen T4:

Laadtijd: 24 uur

Noodverlichting duur: >120 min.

Conform the standards: EN60079

Technical data:

Ex mark: II 2 G Ex db eb mb op is q IIC T5/T4 Gb
 II 2 D Ex tb IIIC T80°C Db

Can be used in zone 1 and zone 2

Ambient temperature range (T4): -25°C to +55°C

Ambient temperature range (T5): -25°C to +40°C

Degree of protection: IP66

Rated voltage 100 ~ 250 VAC 50/60 Hz.

Lamp: 1 or 2 pieces. LED unit 30 Watt / color 5700 K

Cable entree - 3 pcs M25

Material cover: Polycarbonate

Version with battery for emergency lighting, only T4

Charging time: 24 hours

Emergency light duration: >120 min.

Meets the standards: EN60079

Afbeelding Illustration	Materiaal	Material	Type
 Standaard / Standard - 1 x 30 Watt	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1361/23-1 LED30W2 Z.1361/40-1 LED30W2 Z.1361/60-1 LED30W2
 Standaard / Standard - 2 x 30 Watt	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1362/23-2 LED30W2 Z.1362/40-2 LED30W2 Z.1362/60-2 LED30W2
 Noodarmatuur / Emergency - 1 x 30 Watt	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1361/23-1 LED30W2-YJ Z.1361/40-1 LED30W2-YJ Z.1361/60-1 LED30W2-YJ
 Noodarmatuur / Emergency - 2 x 30 Watt	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1362/23-2 LED30W2-YJ Z.1362/40-2 LED30W2-YJ Z.1362/60-2 LED30W2-YJ
 Inlegarmatuur / Insert fixture - 1 x 30 Watt	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1361/123-1 LED30W2 Z.1361/140-1 LED30W2 Z.1361/160-1 LED30W2
 Inlegarmatuur / Insert fixture - 2 x 30 Watt	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1362/223-2 LED30W2 Z.1362/240-2 LED30W2 Z.1362/260-2 LED30W2
 Nood-inleg armatuur/Emergency-insert - 1x30 W	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1361/123-1 LED30W2-YJ Z.1361/140-1 LED30W2-YJ Z.1361/160-1 LED30W2-YJ
 Nood-inleg armatuur/Emergency-insert - 2x30 W	Metaal-Poeder coating wit RVS 304 RVS 316	Steel-white - coated SS 304 SS 316	Z.1362/223-2 LED30W2-YJ Z.1362/240-2 LED30W2-YJ Z.1362/260-2 LED30W2-YJ